

CFMM-S-72C

Ceramic Flat Membrane Module

Introduction

◆ Based on the inherent advantages of ceramic membranes — high flux, high filtration precision, excellent antifouling performance, corrosion resistance and long service life — innovative integration is adopted with a stackable tower structure and full corrosion-resistant stainless steel construction. The modular design allows single-layer maintenance, doubles the packing density for a compact and high-efficiency layout, and eliminates failure-prone components to completely prevent leakage.

Application

- ◆ Drinking water purification
- ◆ Municipal wastewater treatment
- ◆ Industrial wastewater treatment
- ◆ Membrane bioreactor (MBR) system
- ◆ Seawater & brackish water desalination pretreatment

Features

- ◆ High Packing Density (72m²)
- ◆ Modular Design, Easy Installation
- ◆ Good Water Quality (turbidity ≤0.1 NTU)
- ◆ PPO Material Corrosion-resistant
- ◆ Membrane Element Assembled Individually
- ◆ Stable Chemical Performance

Product Specifications

Model	CFMM-S-18C
Ceramic Membrane Model	CFM-616A-M0.1
Membrane Area (m ²)	72
Size (mm)	960*780*1600
Weight (kg)	400
Membrane Frame Material	Stainless steel/PPO
Number of Membrane (pcs)	408

